

ACCENT C7 - MODEL: ELC7


Linear Luminaires



PROJECT:

TYPE:

Product Image



Line Drawing



Product Description

The Beacon X3 series lighting fixtures use a design of evenly spaced light sources with strong light efficiency and long lifespan, ensuring uniform light output and no shadows. Linear lighting fixtures meet the requirements of LEED outdoor lighting power consumption design. The slender lamp body and clean appearance ensure easy assembly to the exterior wall. BEACON lighting fixtures come from the bottom of the lighting equipment and are flexible to meet the power cable requirements of the project. IP66 waterproof rating. DC24V ensures effective transmission of power and signals, with low line losses. DMX512 dimming control with automatic programming function. The bracket is easy to install and disassemble, simplifying maintenance difficulty. At the same time, the vertical direction is subjected to the clamping force of the bracket, which effectively ensures that the lamp is not prone to falling in the vertical direction. Unique fixed bracket design, integrated with safety rope, improves the safety factor of use.

Product Features

- Body Material: PC94V0
- Optical System: Integrated extrusion lens
- Finish: /
- Adjustable Angle: /
- Accessories: Fixed bracket/rotating bracket
- Certification: CQC
- IP Rating: IP66
- Insulation Level: Class III
- Operating Temperature: -20°C~50°C

Product Specifications

- LED Type: SMD
- Light Power: 12W Max / 1000mm
- Source LM: 3000K 1320LM
- LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 2700K / 3000K / 4000K / Ra80
- SDCM: 3 SDCM
- Input: 24V DC
- Dimming: On-off / DMX512
- Net Weight: 0.95Kg without packing

Order Model

Model	Length (mm)	Power (W)	LEDs	Max Lumens(lm)	Control Systems	Beam	Phase Controller	CCT	Finish
ELC703	250	03 3(Max)	18	177	ET ON-OFF 24V DC Power Supply	2 20° 4 40° 6 60°	0 W/O hase	27 2700K	BK Black
ELC705	500	06 6(Max)	36	358				30 3000K	
ELC710	1000	12 12(Max)	72	667				40 4000K	

Example: ELC710-12ET-2030BK

ACCENT C7 - MODEL: ELC7

Linear Luminaires















PROJECT:

TYPE:

Model	Length (mm)	Power(W)	LEDs	Max Lumens(lm)	Control Systems	Beam	Phase Controller	CCT	Finish
ELC703	250	03 3(Max)	18	177	MT DMX512 Dimming 24V DC Power Supply	2 20° 4 40° 6 60°	1 1 Phase 6 6 Phase	27 2700K	BK Black
ELC705	500	06 6(Max)	36	358				30 3000K	
ELC710	1000	12 12(Max)	72	667				40 4000K	

Example: ELC710-12MT-2130BK

Accessory

Item	Description	Pic	Description Dimensions	Quantity Suggested
ELC7-FB001	Fix Bracket			n + 1 (n=Luminare QTY.)
ELC7-AB001	Adjust Bracket			2n (n=Luminare QTY.)
ELF5-PC-CT002F	ET Female connector			1 pc per 14m
ELF5-PC-CT002M	ET Male connector			1 pc per 14m
ELF5-CC-CT002F	MT Female connector			1 pc per 14m
ELF5-CC-CT002M	MT Male connector			1 pc per 14m

ACCENT C7 - MODEL: ELC7


Linear Luminaires

WAC

PROJECT:

TYPE:

LIGHT DISTRIBUTION@3000K LUMINAIRE DATA



MODEL: ELC710-12ET-2030BK


BEAM ANGLE: 20°

POWER: 12W

LUMENS: 515 lm

CBCP: /

EFFICACY: 46.1 lm/W



MODEL: ELC710-12ET-4030BK


BEAM ANGLE: 40°

POWER: 12W

LUMENS: 667 lm

CBCP: /

EFFICACY: 60.2 lm/W



MODEL: ELC710-12ET-6030BK

BEAM ANGLE: 60°

POWER: 12W

LUMENS: 477 lm

CBCP: /

EFFICACY: 42.9 lm/W