

VIEW-HORIZONTAL - MODEL: ELV203

Linear Luminaires

WAC

PROJECT:

TYPE:

Product Image

Line Drawing



Product Description

The Beacon View Horizontal series lighting fixtures are equipped with high-quality chips with strong light efficiency and long lifespan, as well as lenses with unique optical performance. Combined with equidistant layout design, they ensure uniform light output. IP66 waterproof rating and DMX512 dimming control, View Horizontal series lamps come out from the side, and a specially configured Gore breathing valve can effectively balance internal and external air pressure to prevent condensation, meeting the requirements of LEED outdoor lighting power consumption design.

Product Features

- Body Material: Aluminum extruded lamp body, aluminum die cast end cover
- Optical System: Lens
- Finish: Static electricity powder coating
- Projection direction: /
- Accessories/brackets: Stainless steel fixed bracket ensures precise aiming and continuous lighting
- Certification: CQC
- IP Rating: IP66
- Insulation Level: Class III
- Operating Temperature: -20°C~50°C

Product Specifications

- LED Type: High Power
- LED Power: 6.6W (Max) /300mm
- Source Lm: 3000K 483lm ;4000K 513lm
- LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 3000K, Ra80 / 4000K, Ra80
- SDCM: 3 SDCM
- Input: 24V DC
- Dimming: ON-OFF or DMX512 dimming control
- Net Weight: 0.45Kg without packing

Order Model

Model	Length	Power	LED Quantity	Max Lumens	Control Systems	Beam	Power Feed type	CCT	Finish
ELV203-07	300mm	7W(Max)	3	455 LM	ET ON-OFF 24V DC Power Supply MT DMX512 Dimming 24V DC Power Supply	C 60°×100°	S Side	30 3000K 40 4000K	B Black

Example: ELV203-07ET-CS30-B

VIEW-HORIZONTAL - MODEL: ELV203


Linear Luminaires

WAC

PROJECT:

TYPE:

LIGHT DISTRIBUTION@3000K LUMINAIRE DATA



MODEL:	ELV203-07ET-CS30-B
BEAM ANGLE:	60° x 100°
POWER:	8.1W/300mm
LUMENS:	443lm
CBCP:	/
EFFICACY:	54.6lm/W

VIEW-HORIZONTAL - MODEL: ELV206

Linear Luminaires

WAC

PROJECT:

TYPE:

Product Image



Line Drawing



Product Description

The Beacon View Horizontal series lighting fixtures are equipped with high-quality chips with strong light efficiency and long lifespan, as well as lenses with unique optical performance. Combined with equidistant layout design, they ensure uniform light output. IP66 waterproof rating and DMX512 dimming control, View Horizontal series lamps come out from the side, and a specially configured Gore breathing valve can effectively balance internal and external air pressure to prevent condensation, meeting the requirements of LEED outdoor lighting power consumption design.

Product Features

- Body Material: Aluminum extruded lamp body, aluminum die cast end cover
- Optical System: Lens
- Finish: Static electricity powder coating
- Projection direction: /
- Accessories/brackets: Stainless steel fixed bracket ensures precise aiming and continuous lighting
- Certification: CQC
- IP Rating: IP66
- Insulation Level: Class III
- Operating Temperature: -20°C~50°C

Product Specifications

- LED Type: High Power
- LED Power: 13.2W (Max) /600mm
- Source Lm: 3000K 966lm ;4000K 1026lm
- LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 3000K, Ra80 / 4000K, Ra80
- SDCM: 3 SDCM
- Input: 24V DC
- Dimming: ON-OFF or DMX512 dimming control
- Net Weight: 0.9Kg without packing

Order Model

Model	Length	Power	LED Quantity	Max Lumens	Control Systems	Beam	Power Feed type	CCT	Finish
ELV206-14	600mm	14W(Max)	6	890 LM	ET ON-OFF 24V DC Power Supply MT DMX512 Dimming 24V DC Power Supply	C 60°×100°	S Side	30 3000K 40 4000K	B Black

Example: ELV206-14ET-CS30-B

VIEW-HORIZONTAL - MODEL: ELV206


Linear Luminaires

WAC

PROJECT:

TYPE:

LIGHT DISTRIBUTION@3000K LUMINAIRE DATA



MODEL:	ELV206-14ET-CS30-B
BEAM ANGLE:	60 °×100 °
POWER:	16.3W/600mm
LUMENS:	890lm
CBCP:	/
EFFICACY:	54.6lm/W

VIEW-HORIZONTAL - MODEL: ELV209

Linear Luminaires

WAC

PROJECT:

TYPE:

Product Image



Line Drawing



Product Description

The Beacon View Horizontal series lighting fixtures are equipped with high-quality chips with strong light efficiency and long lifespan, as well as lenses with unique optical performance. Combined with equidistant layout design, they ensure uniform light output. IP66 waterproof rating and DMX512 dimming control, View Horizontal series lamps come out from the side, and a specially configured Gore breathing valve can effectively balance internal and external air pressure to prevent condensation, meeting the requirements of LEED outdoor lighting power consumption design.

Product Features

- Body Material: Aluminum extruded lamp body, aluminum die cast end cover
- Optical System: Lens
- Finish: Static electricity powder coating
- Projection direction: /
- Accessories/brackets: Stainless steel fixed bracket ensures precise aiming and continuous lighting
- Certification: CQC
- IP Rating: IP66
- Insulation Level: Class III
- Operating Temperature: -20°C~50°C

Product Specifications

- LED Type: High Power
- LED Power: 19.8W (Max) /900mm
- Source Lm: 3000K 1449lm ;4000K 1539m
- LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 3000K, Ra80 / 4000K, Ra80
- SDCM: 3 SDCM
- Input: 24V DC
- Dimming: ON-OFF or DMX512 dimming control
- Net Weight: 1.35Kg without packing

Order Model

Model	Length	Power	LED Quantity	Max Lumens	Control Systems	Beam	Power Feed type	CCT	Finish
ELV209-21	900mm	21W(Max)	9	1329 LM	ET ON-OFF 24V DC Power Supply MT DMX512 Dimming 24V DC Power Supply	C 60°×100°	S Side	30 3000K 40 4000K	B Black

Example: ELV209-21ET-CS30-B

VIEW-HORIZONTAL - MODEL: ELV209


Linear Luminaires

WAC

PROJECT:

TYPE:

LIGHT DISTRIBUTION@3000K LUMINAIRE DATA



MODEL:	ELV209-21ET-CS30-B
BEAM ANGLE:	60 °×100 °
POWER:	24.4W/900mm
LUMENS:	1329lm
CBCP:	/
EFFICACY:	54.5lm/W

VIEW-HORIZONTAL - MODEL: ELV212

Linear Luminaires



PROJECT:

TYPE:

Product Image



Line Drawing



Product Description

The Beacon View Horizontal series lighting fixtures are equipped with high-quality chips with strong light efficiency and long lifespan, as well as lenses with unique optical performance. Combined with equidistant layout design, they ensure uniform light output. IP66 waterproof rating and DMX512 dimming control, View Horizontal series lamps come out from the side, and a specially configured Gore breathing valve can effectively balance internal and external air pressure to prevent condensation, meeting the requirements of LEED outdoor lighting power consumption design.

Product Features

- Body Material: Aluminum extruded lamp body, aluminum die cast end cover
- Optical System: Lens
- Finish: Static electricity powder coating
- Projection direction: /
- Accessories/brackets: Stainless steel fixed bracket ensures precise aiming and continuous lighting
- Certification: CQC
- IP Rating: IP66
- Insulation Level: Class III
- Operating Temperature: -20°C~50°C

Product Specifications

- LED Type: High Power
- LED Power: 26.4W (Max) /1200mm
- Source Lm: 3000K 1932lm ;4000K 2052m
- LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 3000K, Ra80 4000K, Ra80
- SDCM: 3 SDCM
- Input: 24V DC
- Dimming: ON-OFF or DMX512 dimming control
- Net Weight: 1.8Kg without packing

Order Model

Model	Length	Power	LED Quantity	Max Lumens	Control Systems	Beam	Power Feed type	CCT	Finish
ELV212-28	1200mm	28W(Max)	12	1772 LM	ET ON-OFF 24V DC Power Supply MT DMX512 Dimming 24V DC Power Supply	C 60°×100°	S Side	30 3000K 40 4000K	B Black

Example: ELV212-28ET-CS30-B

VIEW-HORIZONTAL - MODEL: ELV212


Linear Luminaires

WAC

PROJECT:

TYPE:

LIGHT DISTRIBUTION@3000K LUMINAIRE DATA



MODEL:	ELV212-28ET-CS30-B
BEAM ANGLE:	60 °×100 °
POWER:	32.5W/1200mm
LUMENS:	1772lm
CBCP:	/
EFFICACY:	54.5lm/W