

FUEGO INDICATOR - MODEL: EIR2SF

In-ground Luminaires

WAC


PROJECT:

TYPE:

Product Image



Line Drawing



Product Description

The overall stainless steel material of the FUEGO Indicator is precision cast, with a circular appearance and an IP68 protection level, suitable for underwater environments. It has an IK08 impact resistance level and can withstand pressure of 500kg. The design of stainless steel shrapnel can support wall or tube lamp installation.

Product Features

- Body Material: Overall stainless steel material
- Optical System: Lens
- Finish: /
- Adjustable Angle: /
- Accessories: /
- Certification: CQC
- IP Rating: IP68
- Insulation Level: Class III
- Operating Temperature: -20°C~50°C

Product Specifications

- LED Type: High Power
- Power: 4W(Max)
- Source Lm: 3000K 500lm ;4000K 500lm;Amber;Blue
- LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 3000K,Ra85 / 4000K,Ra85
- SDCM: 3 SDCM
- Input: 9-15V/AC
- Dimming: ON-OFF
- Net Weight: 0.7Kg without packing

Order Model

Model	comment	Power (W)	LEDs (quantity)	Max Lumens (Lm)	Control Systems	Beam	CCT	Finish
EIR2S	F Frame	04 4(Max)	1	170	ET ON-OFF 9-15V/AC Power Supply	2 25°	30 3000K 40 4000K A Amber B Blue	SS Stainless Steel

Example: EIR2SF-04ET-240SS

WAC Lighting

www.waclighting.com (US)
www.waclighting.com.cn (China)

Headquarters

44 Harbor Park Drive • Port Washington, NY
Phone (516) 515.5000 • Fax (516) 515.5050

WAC Lighting(Shanghai)

14,Lane 299, Bi Sheng Road,Shanghai 201204
Phone (86.21) 3393.3558 • Fax (86.21) 3362.1598

WAC Lighting reserves the right to periodically design and update products.2024-01-24

FUEGO INDICATOR - MODEL: EIR2SF

In-ground Luminaires

WAC


PROJECT:

TYPE:

Accessory

Item	Pic	Small Version
Single Directional (Round Frame)		EIR2SF-SDRF-SS
Double Directional (Round Frame)		EIR2SF-DDRF-SS

LIGHT DISTRIBUTION@3000K LUMINAIRE DATA



MODEL:	EIR2SF-04ET-230SS
BEAMANGLE	25°
POWER:	6W (Max)
LUMENS:	170 lm
CBCP:	/
EFFICACY:	28 lm /W