# **LEDME - MODEL: WL110**

# Step And Wall Luminaires




PROJECT:	TYPE:	

## **Product Image**



### **Line Drawing**



### **Product Description**

LED lights designed to highlight architectural aesthetics, LEDme<sup>®</sup> The design of the series of lamps originates from the seamless integration structure with the wall. Efficient energy conservation and optimized light output increase the safety and style of stairs, while maintaining minimal glare on walls and corridors. IP65 can also solve indoor and outdoor lighting solutions in damp places. 220V AC direct wiring is available.

#### **Product Features**

• Body Material: Aluminum alloy die-casting

• Optical System: Matte glass

• Finish: Static electricity powder coating

Adjustable Angle: /
Accessories: /
Certification: CCC
IP Rating: IP65
Insulation Level: Class I

• Operating Temperature:-20°C~50°C

#### **Product Specifications**

Opening size: 118x74mm
 LED Type: SMD
 Power: 3.22W
 Source Lm: 3000K 190lm

LED Lifetime: >40000h-L70 / B10-Ta25°C(LM-80 / TM-21)
 CCT/CRI: 2700K,Ra80;3000K,Ra80;4000K,Ra80

- CDCM 2700K, Kaoo, 5000K, Kaoo, -

SDCM: 3SDCM
Input: 220V AC/50Hz
Dimming: ON-OFF

• Net Weight: 0.7Kg without packing

## **Order Model**

Model		Power (W)	Max Lumens (lm)	Control Systems	Beam	CCT	Finish
WL110	LD04	3.2	6	<b>E</b> ON-OFF 220V AC Power Supply	<b>D</b> Directional	27 2700K 30 3000K 40 4000K	WT White BK Black BZ Bronze BN Brushed Nickel

Example: WL110-LD04E-D30WT


# **LEDME - MODEL: WL110**

Step And Wall Luminaires



PROJECT:	TYPE:
Accessory	

### LIGHT DISTRIBUTION@3000K LUMINAIRE DATA



 MOEDL:
 WL110-LD04E-D30WT

 BEANANGLE:
 /

 POWER:
 4W

 LUMENS:
 6lm

 CBCP:
 /

 EFFICACY:
 1.5 lm / W