

ULTRA TUNABLE - MODEL: DLN33

3" CCT Tunable Downlight

WAC


PROJECT:

TYPE:

Product Image



Line Drawing



Product Description

The ULTRA Tunable series LED circular narrow-edge embedded downlight has a total height of only 55mm. Through glass sealing design, it can be used for anti fog or low ceiling spaces. The lighting fixtures adopt modular design, allowing for free disassembly and replacement of reflectors or mounting frames on site, thereby achieving free switching of various specifications and lighting methods. After installation, they are perfectly integrated with the ceiling. In terms of optics, a new hidden light technology is adopted and equipped with color temperature adjustable function, which is mainly suitable for indoor places such as hotels, villas, and commercial spaces.

Product Features

- Body Material: Aluminum alloy die-casting
- Optical System: Lens+ SUBOROSA optical system
- Finish: Static electricity powder coating
- Adjustable Angle: Horizontal 0-360°, vertical non adjustable
- Accessories/brackets: As attached
- Certification: CCC
- IP Rating: IP20
- Insulation Level: Class II
- Operating Temperature: -20°C~40°C

Product Specifications

- Cut-out: Ø78
- Ceiling Thickness: 5mm~25mm
- Shielding Angle: 35°
- LED Type: COB
- Source Lm: 1300LM
- LED Lifetime: >36000h-L70/B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 2700K~6000K Tunable, CRI≥Ra90
- Input: 220V AC / 50Hz
- Dimming: DALI
- Net Weight: 0.3Kg without packing

Order Model

| Model | Size | Trim | LED | Driver | Beam | CCT | Reflector | Finish |
|-------------------------------------|---------|--------------------|---------------------|-----------------------|-------|--------------------------------------|-------------------------------------|--|
| DLN Downlight N series | 3 3" | 3 Round Trim | LM13 COB 13W | N NO DRIVER A DALI | 1 18° | CC 2700-6000K (Tunable) | B Black S Specular | WT White BK Black |
| | | | | | 2 28° | | | |
| | | | | | 3 36° | | | |
| | | | | | 5 50° | | | |

Example: DLN33-LM13A-2CCSWT

Note: 18° factory default with borderless honeycomb grille

ULTRA TUNABLE - MODEL: DLN33

3" CCT Tunable Downlight



PROJECT:

TYPE:


LENS-12-HCL-ULTRA

Borderless honeycomb grille




Note: Accessories need to be ordered separately. The 18 ° factory default comes with an endless honeycomb grille, which is installed on the back of the reflector.


LIGHT DISTRIBUTION@3000K LUMINAIRE DATA




| | |
|--------------------|--------------------|
| MODEL: | DLN33-LM13A-ICCSWT |
| BEAM ANGLE: | 18 ° |
| POWER: | 16W |
| LUMENS: | 688lm |
| CBCP: | 4588cd |
| EFFICACY: | 43lm/W |



| | |
|--------------------|--------------------|
| MODEL: | DLN33-LM13A-2CCSWT |
| BEAM ANGLE: | 28 ° |
| POWER: | 16W |
| LUMENS: | 1042lm |
| CBCP: | 3976cd |
| EFFICACY: | 65lm/W |



| | |
|--------------------|-------------------|
| MODEL: | DL33-LM13A-3CCSWT |
| BEAM ANGLE: | 36 ° |
| POWER: | 16W |
| LUMENS: | 923lm |
| CBCP: | 2309cd |
| EFFICACY: | 58lm/W |



| | |
|--------------------|--------------------|
| MODEL: | DLN33-LM13A-5CCSWT |
| BEAM ANGLE: | 50 ° |
| POWER: | 16W |
| LUMENS: | 740lm |
| CBCP: | 902cd |
| EFFICACY: | 46lm/W |