

FUEGO INDICATOR - MODEL: EIS2NF

In - ground Luminaires

WAC


PROJECT:

TYPE:

Product Image



Line Drawing



Product Description

FUEGO Indicator overall stainless steel, seiko casting, square appearance, IP68 protection grade, suitable for underwater environment, IK08 anti-impact grade, can resist pressure 500kg. Stainless steel shrapnel is designed to support wall or downlight mounting.

Product Features

- Body Material: Integral stainless steel
- Optical System: Lens optical system
- Finish: /
- Adjustable Angle: /
- Accessories: /
- Certification: CQC
- IP Rating: IP68
- Insulation Level: Class II
- Operating Temperature: -20°C~50°C

Product Specifications

- Lamp Power: 2W(Max)
- LED Type: HP LED
- Source Lm: 3000K 260LM; 4000K 260LM; Amber; Blue;
- LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 3000K, Ra85/4000K, Ra85
- SDCM: 3 SDCM
- Input: 9-15V AC
- Dimming: ON-OFF
- Net Weight: 0.3Kg without packing

Order Model

Model	Comment	Power(W)	LED(quantity)	Max Lumens	Control	Systems	Beam	CCT,	Finish
EIS2N	F Frame	02 2(Max)	1	80	ET	ON-OFF 9-15V/AC Power Supply	5 50°	30 3000K 40 4000K A Amber B Blue	SS Stainless Steel

Example: EIS2NF-02ET-540SS

FUEGO INDICATOR - MODEL: EIS2NF


In - ground Luminaires

WAC

PROJECT:

TYPE:

LIGHT DISTRIBUTION@3000K LUMINAIRE DATA



MODEL:	EIS2NF-02ET-530SS
BEAM ANGLE:	50°
POWER:	3W (Max)
LUMENS:	80lm
CBCP:	/
EFFICACY:	23lm/W