

# FUEGO INDICATOR - MODEL: EIS4NF

In - ground Luminaires

# WAC


PROJECT:

TYPE:

## Product Image



## Line Drawing



## Product Description

FUEGO Indicator overall stainless steel, seiko casting, square appearance, IP68 protection grade, suitable for underwater environment, IK08 anti-impact grade, can resist pressure 500kg. Embedded cylinder installation.

## Product Features

- Body Material: Overall stainless steel, PC embedded cylinder
- Optical System: Lens optical system
- Finish: /
- Adjustable Angle: /
- Accessories: /
- Certification: /
- IP Rating: IP68
- Insulation Level: Class III
- Operating Temperature: -20°C~50°C

## Product Specifications

- Lamp Power: 2W(Max)
- LED Type: HP LED
- Source Lm: 3000K 260LM; 4000K 260LM; Amber; Blue;
- LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 3000K, Ra85/4000K, Ra85
- SDCM: 3 SDCM
- Input: 9-15V AC
- Dimming: ON-OFF
- Net Weight: 0.3Kg without packing

## Order Model

Model	Comment	Power(W)	LED(quantity)	Max Lumens	Control	Systems	Beam	CCT,	Finish
<b>EIS4N</b>	<b>F</b> Frame	<b>02</b> 2(Max)	<b>1</b>	<b>80</b>	<b>ET</b>	ON-OFF 9-15V/AC Power Supply	<b>5</b> 50°	<b>30</b> 3000K <b>40</b> 4000K <b>A</b> Amber <b>B</b> Blue	<b>SS</b> Stainless Steal

Example: EIS4NF-02ET-540SS

# FUEGO INDICATOR - MODEL: EIS4NF


In - ground Luminaires

# WAC

PROJECT:

TYPE:

## LIGHT DISTRIBUTION@3000K LUMINAIRE DATA



<b>MODEL:</b>	EIS4NF-02ET-530SS
<b>BEAM ANGLE:</b>	50°
<b>POWER:</b>	3W (Max)
<b>LUMENS:</b>	80 lm
<b>CBCP:</b>	/
<b>EFFICACY:</b>	23 lm /W