

# OCULARC - MODEL: ME48S/SR48S

Surface Mounted Luminaires

# WAC


PROJECT :

TYPE :


## Product Image



## Line Drawing



SR48S



ME48S

## Product Description

The Ocularc series surface mounted lamps can be selected for either hole embedded installation or surface magnetic suction installation, making the lamps flexible and compact; Adopting WAC's leading SUBOROSA dimming technology with a built-in 30 ° anti glare angle, achieving the ultimate anti glare effect; Provide 4 fixed angle options to meet the needs of different application environments, which can be widely used in museum and art museum display cabinet spaces.

## Product Features

- Body Material: Aluminum alloy die-casting
- Optical System: Lens+ SUBOROSA optical system
- Finish: Static electricity powder coating
- Adjustable Angle: 0-360°Horizontal 0-90°Vertical
- Accessories: As attached
- Certification: CQC
- IP Rating: IP20
- Insulation Level: Class III
- Operating Temperature: -20°C~40°C

## Product Specifications

- Cut-out: SR48S corresponds to the opening Ø17  
Ceiling 1mm~15mm ;ME48S magnetic suction
- LED Type: HP LED
- Led power: 10W
- Source Lm: 3000K 950LM; 4000K 1000LM;
- LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 3000K/4000K , Ra90 and Ra97(> Ra95)
- SDCM: 3 SDCM
- Input: Constant current 800mA max
- Dimming: External drive
- Net Weight: 0.2Kg without packing

## Order Model

Model	LED	Dimming	Beam	CRI	CCT	Finish
ME48S	LD10 LED 10W	N Single wire *	1 15°	9 90 A 97	30 3000K 40 4000K	BK Black
SR48S						
Ocularc						
ME48S	LD10	N	2	9	30	BK

Example : ME48SLD10-N-2930BK

Note: Except for the 15 ° built-in honeycomb, the rest do not include honeycomb;

\*The lighting fixtures do not include driving appliances and need to be ordered separately (the dimming method is determined by the appliances).  
The exposed wire of the original lighting fixture is about 0.5m long

# OCULARC - MODEL: ME48S/SR48S

Surface Mounted Luminaires



PROJECT :

TYPE :

## Accessory


### LD-070MA14D-LF-C

Special electrical appliances: Input 220V~240VAC/50Hz, output 700mA (power 9W), 8-12V Supports 0-10V dimming and can drive 1 display cabinet light  
size (L\*W\*H) : 115\*43\*25 , mm




Note: Electrical appliances need to be ordered separately, excluding wires


## LIGHT DISTRIBUTION@3000K LUMINAIRE DATA




MODEL :	SR48SLD10-N-1930BK
BEAM ANGLE :	15°
POWER :	10W
LUMENS :	397lm
CBCP :	3556cd
EFFICACY :	35lm/W



MODEL :	SR48SLD10-N-2930BK
BEAM ANGLE :	24°
POWER :	10W
LUMENS :	471lm
CBCP :	2018cd
EFFICACY :	47lm/W



MODEL :	SR48SLD10-N-3930BK
BEAM ANGLE :	36°
POWER :	10W
LUMENS :	427lm
CBCP :	953cd
EFFICACY :	43lm/W



MODEL :	SR48SLD10-N-6930BK
BEAM ANGLE :	60°
POWER :	10W
LUMENS :	402lm
CBCP :	418cd
EFFICACY :	40lm/W