

# LIGHT PANEL - MODEL: OGP20211

Panel Luminaires

# WAC


PROJECT :

TYPE :

Product Image



Line Drawing



## Product Description

WAC universal lamp panel, using aluminum profile lamp body, has a simple and beautiful appearance, and has good heat dissipation performance. Using anti glare prism optics, no visible glare, UGR less than 19, with good anti glare performance and light uniformity. Using LED light source color consistency control, Ra90, no flicker, high light efficiency and energy saving. It has a comfortable lighting effect and is suitable for lighting applications in commercial, office, classroom, and other places.

## Product Features

- Body Material: Aluminum alloy extruded lamp body
- Optical System: Lens+grille
- Finish: Static electricity powder coating
- Adjustable Angle: /
- Accessories: Suspension rod assembly
- Certification: CCC
- IP Rating: IP40
- Insulation Level: Class I
- Operating Temperature: -20°C~40°C

## Product Specifications

- Shielding angle: /
- LED Type: SMD LED
- Source Lm: 3000K:36W 4680lm;40W 5200lm  
4000K:36W 4860lm;40W 5400lm  
5000K:36W 4860lm;40W 5400lm
- LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 3000K/ 4000K/5000K/Ra90
- SDCM: 5 SDCM
- Input: 220~240V/AC , 50Hz
- Dimming: ON-OFF/0-10V  
(Conduct compatibility testing in advance)
- Net Weight: 3.8Kg without packing

## Order Model

| Model       | Size<br>(mm)           | Power<br>(W)                   | Driver                                    | Beam Down         | CCT   | Finish          |
|-------------|------------------------|--------------------------------|---|-------------------|---|-----------------|
| <b>OGP2</b> | <b>0211</b> 295*1195mm | <b>36</b> 36W<br><b>40</b> 40W | <b>E</b> ON-OFF<br><b>D</b> 0-10V Dimming | <b>G</b> (Grille) | <b>30</b> 3000K<br><b>40</b> 4000K<br><b>50</b> 5000K | <b>WT</b> White |

Example : OGP20211-36E-G50WT

Note: 9 classroom lights for regular classrooms, installation method: lifting

# LIGHT PANEL - MODEL: OGP20211


Panel Luminaires

# WAC


PROJECT :

TYPE :

## LIGHT DISTRIBUTION@5000K LUMINAIRE DATA



**MODEL :** OGP20211-36E-G50WT  
**BEAM ANGLE :** /  
**POWER :** 39.12W  
**LUMENS :** 4109.1lm  
**CBCP :** /  
**EFFICACY :** 105.04lm/W



**MODEL :** OGP20211-40E-G50WT  
**BEAM ANGLE :** /  
**POWER :** 43.1W  
**LUMENS :** 4448.6lm  
**CBCP :** /  
**EFFICACY :** 103.22lm/W