

PLANA PRO - MODEL: DWP31

Recessed Ceiling Luminaires

WAC


PROJECT:

TYPE:

Product Image



Line Drawing



Product Description

PLANA PRO downlight using LiteBrush optical system, with RGBW chip, can achieve magic color wall washing, while having a good anti-glare effect. Mainly applicable to hotels and commercial areas.

Product Features

- Body Material: Aluminum alloy die-casting
- Optical System: LiteBrush® wall wash system
- Finish: Static electricity powder coating
- Adjustable Angle: /
- Accessories: /
- Certification: CCC
- IP Rating: IP20
- Insulation Level: Class I
- Operating Temperature: -20°C~40°C

Product Specifications


- Cut-out: Ø93mm
- Ceiling Thickness: 1mm~35mm
- Shielding Angle: 35°
- LED Type: RGBW 4in1
- LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: RGB+3000K Ra90
- Input: 24V DC
- Dimming: DMX512
- Net Weight: 1.0Kg without packing

Order Model

Model	Size	Trim	LED	Driver	CCT	Beam	Reflector	Finish
DWP	3	1	LD14	M	F3	W Wash	B Black	WT White
Downlight	3"	Round Trim	14W	24V DMX512	RGBW(3000K)			BK Black
Wallwasher								
P series								

Example: DWP31-LD14M-F3WBBK

LIGHT DISTRIBUTION



WAC Lighting
www.waclighting.com (US)
www.waclighting.com.cn (China)

Headquarters
 44 Harbor Park Drive • Port Washington,
 NY Phone (516) 515.5000 • Fax (516)

WAC Lighting(Shanghai)
 14,Lane 299, Bi Sheng Road,Shanghai 201204
 Phone (86.21) 3393.3558 • Fax (86.21)

PLANA PRO - MODEL: DWP41

Recessed Ceiling Luminaires




PROJECT:

TYPE:

Product Image



Line Drawing



Product Description

PLANA PRO downlight using LiteBrush optical system, with RGBW chip, can achieve magic color wall washing, while having a good anti-glare effect. Mainly applicable to hotels and commercial areas.

Product Features

- Body Material: Aluminum alloy die-casting
- Optical System: LiteBrush® wall wash system
- Finish: Static electricity powder coating
- Adjustable Angle: /
- Accessories: /
- Certification: CCC
- IP Rating: IP20
- Insulation Level: Class I
- Operating Temperature: -20°C~40°C

Product Specifications


- Cut-out: Ø116mm
- Ceiling Thickness: 1mm~35mm
- Shielding Angle: 35°
- LED Type: RGBW 4in1
- LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: RGB+3000K Ra90
- Input: 24V DC
- Dimming: DMX512
- Net Weight: 1.45Kg without packing

Order Model

Model	Size	Trim	LED	Driver	CCT	Beam	Reflector	Finish
DWP	4	1	LD24	M	F3	W Wash	B Black	WT White
Downlight	4"	Round Trim	24W	24V DMX512	RGBW(3000K)			BK Black
Wallwasher								
P series								

Example: DWP41-LD24M-F3WBBK

LIGHT DISTRIBUTION



WAC Lighting
www.waclighting.com (US)
www.waclighting.com.cn (China)

Headquarters
 44 Harbor Park Drive • Port Washington,
 NY Phone (516) 515.5000 • Fax (516)

WAC Lighting(Shanghai)
 14,Lane 299, Bi Sheng Road,Shanghai 201204
 Phone (86.21) 3393.3558 • Fax (86.21)