

ULTRA - MODEL: SLN32

Ceiling Mount Luminaires




PROJECT:

TYPE:

Product Image



Line Drawing



Product Description

The ULTRA series LED circular exposed tube lamp adopts a modular design, and on-site lamps can be freely disassembled and replaced with reflectors and lamp bodies, thereby achieving free switching of various specifications and lighting methods. In terms of optics, a brand new hidden light technology is adopted, which has good anti glare performance and color consistency control, and has a comfortable lighting effect. It is mainly suitable for indoor places such as hotels, villas, and commercial spaces.

Product Features

- Body Material: Aluminum alloy die-casting body
- Optical System: Lens+ Anti glare reflector
- Finish: Static electricity powder coating
- Projection direction: /
- Accessories/Brackets: See accessory list
- Certification: CCC
- IP Rating: IP20
- Insulation Level: Class II
- Operating Temperature: -20°C~40°C

Product Specifications

- Shielding Angle: 35°
- LED Type: COB
- Source Lm: 3000K 1000LM,4000K 1100LM;
2700K: 8W 682 lm; 7W 758 lm; 10W 1080 lm; 13W 1404 lm
3000K: 8W 720 lm; 7W 800 lm; 10W 1150 lm; 13W 1495 lm
3500K: 8W 752 lm; 7W 835 lm; 10W 1195 lm; 13W 1554 lm
4000K: 8W 765 lm; 7W 850 lm; 10W 1210 lm; 13W 1573 lm
5000K: 8W 774 lm; 7W 860 lm; 10W 1220 lm; 13W 1586 lm
- LED Lifetime: >36000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 2700K/3000K/3500K/4000K/5000K, CRI≥90
- Input: 220V AC /50Hz
- Dimming: No Dimming/0-10V(Must conduct compatibility testing with the project site in advance)
- Net Weight: 0.36Kg without packing

Order Model

Model	Size	Trim	LED	Driver	Beam	CCT	Reflector	Finish
SLN	3	2	LM08 COB 8W	E On-Off	S 8°	27 2700K	B Black	WT
Surface	3"	Ronnd	LM07 COB 7W	D 0-10V	N 13°	30 3000K	S Specular	White
Mounted		Trimless	LM10 COB 10W	Dimming	1 18°	35 3500K		BK
Downlight			LM13 COB 13W		2 28°	40 4000K		Black
N series					3 36°	50 5000K		
					5 50°			

Example: SLN32-LM07E-N30SWT

Note: 8°, 13°, and 18° are factory default with honeycomb grilles.

ULTRA - MODEL: SLN32





Ceiling Mount Luminaires



PROJECT:


TYPE:

Accessory


LENS-11-BEL Striped glass lenses 	LENS-11-BSL-ULTRA Soft glass lenses 	LENS-11-FR Frosted glass lenses 	LENS-11-HCL-ULTRA Borderless honeycomb grille 
--	---	--	---

Note: Up to one optical accessory can be added; Among them, 8 °, 13 °, and 18 ° are factory default with borderless honeycomb grilles.


LIGHT DISTRIBUTION@3000K LUMINAIRE DATA




MODEL:	SLN32-LM07E-N30SWT
BEAM ANGLE:	13 °
POWER:	9W
LUMENS:	466 lm
CBCP:	5571cd
EFFICACY:	52 lm/W




MODEL:	SLN32-LM10E-N30SWT
BEAM ANGLE:	13 °
POWER:	11W
LUMENS:	520 lm
CBCP:	6220cd
EFFICACY:	47 lm/W




MODEL:	SLN32-LM13E-N30SWT
BEAM ANGLE:	13 °
POWER:	16W
LUMENS:	676 lm
CBCP:	8086cd
EFFICACY:	42 lm/W




MODEL:	SLN32-LM07E-130SWT
BEAM ANGLE:	18 °
POWER:	9W
LUMENS:	721 lm
CBCP:	5316cd
EFFICACY:	80 lm/W




MODEL:	SLN32-LM10E-130SWT
BEAM ANGLE:	18 °
POWER:	11W
LUMENS:	817 lm
CBCP:	6028cd
EFFICACY:	74 lm/W



MODEL:	SLN32-LM13E-130SWT
BEAM ANGLE:	18 °
POWER:	16W
LUMENS:	1062 lm
CBCP:	7836cd
EFFICACY:	66 lm/W



MODEL:	SLN32-LM07E-230SWT
BEAM ANGLE:	28 °
POWER:	9W
LUMENS:	715 lm
CBCP:	3052cd
EFFICACY:	79 lm/W




MODEL:	SLN32-LM10E-230SWT
BEAM ANGLE:	28 °
POWER:	11W
LUMENS:	796 lm
CBCP:	3396cd
EFFICACY:	72 lm/W

ULTRA - MODEL: SLN32
Ceiling Mount Luminaires




PROJECT:


TYPE:




MODEL: SLN32-LM13E-230SWT
BEAM ANGLE: 28 °
POWER: 15W
LUMENS: 1035 lm
CBCP: 4511cd
EFFICACY: 69 lm/W




MODEL: SLN32-LM07E-330SWT
BEAM ANGLE: 36 °
POWER: 9W
LUMENS: 643 lm
CBCP: 1497cd
EFFICACY: 71 lm/W




MODEL: SLN32-LM10E-330SWT
BEAM ANGLE: 36 °
POWER: 11W
LUMENS: 804 lm
CBCP: 1857cd
EFFICACY: 73 lm/W




MODEL: SLN32-LM13E-330SWT
BEAM ANGLE: 36 °
POWER: 15W
LUMENS: 1024lm
CBCP: 2375cd
EFFICACY: 68 lm/W




MODEL: SLN32-LM07E-530SWT
BEAM ANGLE: 50 °
POWER: 9W
LUMENS: 425 lm
CBCP: 574cd
EFFICACY: 47 lm/W



MODEL: SLN32-LM10E-530SWT
BEAM ANGLE: 50 °
POWER: 119W
LUMENS: 532 lm
CBCP: 717cd
EFFICACY: 48 lm/W



MODEL: SLN32-LM13E-530SWT
BEAM ANGLE: 50 °
POWER: 15W
LUMENS: 677 lm
CBCP: 914cd
EFFICACY: 45 lm/W



MODEL: SLN32-LM08E-S30SWT
BEAM ANGLE: 8 °
POWER: 10W
LUMENS: 375lm
CBCP: 9280cd
EFFICACY: 38 lm/W