

OCULARC FOCUS - MODEL: SL45F

Mini Track Luminaires(24V)

WAC


PROJECT :

TYPE :

Product Image



Line Drawing



Product Description

The Ocularc Focus series low-voltage track lighting fixtures are suitable for WAC mini track systems, with flexible and compact lighting fixtures; Adopting WAC's leading SUBROSA dimming technology with a built-in 30 ° anti glare angle, achieving the ultimate anti glare effect; It can adjust the beam angle infinitely to meet the needs of different application environments and is widely used in exhibition cabinet spaces in museums and art galleries.

Product Features

- Body Material: Aluminum alloy fixture body, glass optical device
- Optical System: Dual light distribution of lens and SUBROSA reflector
- Finish: Liquid paint, black (BK)
- Adjustable Angle: Horizontal adjustment from 0 ° to 365 °; Vertical 0-90 ° adjustment
- Accessories: As attached
- Certification: CQC
- IP Rating: IP20
- Insulation Level: Class III
- Operating Temperature: -20°C~40°C

Product Specifications

- LED Type: HP LED
- Light power: 1W
- Source Lm: 3000K:105LM; 4000K:110LM
- LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 3000K/4000K, Optional Ra90 or Ra97 (>Ra95)
- SDCM: 3 SDCM
- Input: 24VDC
- Dimming: On boarding knob dimming (range 10%~100%) or ON-OFF (supports system dimming, requires external dimmable constant voltage appliances, and matches the dimming system)
- Net Weight: About 0.06kg, without packaging

Order Model

Model	LED	Dimming	Beam	CRI	CCT	Finish
SL45F Ocularc Focus	LD01 LED 1W	O On-boarding	F 10-40°	9 90	30 3000K	BK Black
		E ON-OFF ^①		A 97	40 4000K	
SL45F	LD01	O	F	9	30	BK

Example : SL45FLD01-O-F930BK

Note: ①Supports system dimming and requires an external dimmable constant voltage device (dimming method is determined by the constant voltage device)

OCULARC FOCUS - MODEL: SL45F

Mini Track Luminaires(24V)



PROJECT :



TYPE :

Accessories

<p>Low voltage track mini track Provide specifications of 1m, 2m, and 3m</p> <p>MT1M-BK-C 1m track MT2M-BK-C 2m track MT3M-BK-C 3m track</p>		<p>Track power supply end MLE-BK-C</p> 
<p>Type I track connector MI-BK-C</p> 		<p>Type L track connector ML-BK-C</p> 


Note: The low-voltage track adopts surface installation and comes with two end caps; If hanging installation is required for low-voltage tracks, please contact WAC.

LIGHT DISTRIBUTION@3000K LUMINAIRE DATA

	<p>MODEL : SL45FLD01-O-F930(min)</p> <p>BEAM ANGLE : 10°</p> <p>POWER : 1.5W</p> <p>LUMENS : 141lm</p> <p>CBCP : 340cd</p> <p>EFFICACY : 9lm/W</p>		<p>MODEL : SL45FLD-O-F930(max)</p> <p>BEAM ANGLE : 40°</p> <p>POWER : 1.5W</p> <p>LUMENS : 37lm</p> <p>CBCP : 78cd</p> <p>EFFICACY : 25lm/W</p>
---	--	---	---

System Dimming Wiring Diagram (Fixture Model: SL45FLD01-E)

This circuit lighting fixture can support system dimming, and the wiring diagram is as follows (the dimming method is determined by the constant voltage electrical appliance). It is necessary to conduct dimming matching tests in advance.



OCULARC FOCUS - MODEL: SL46F

Mini Track Luminaires(24V)

WAC

PROJECT :

TYPE :

Product Image



Line Drawing



Product Description

The Ocularc Focus series low-voltage track lighting fixtures are suitable for WAC mini track systems, with flexible and compact lighting fixtures; Adopting WAC's leading SUBROSA dimming technology with a built-in 30 ° anti glare angle, achieving the ultimate anti glare effect; It can adjust the beam angle infinitely to meet the needs of different application environments and is widely used in exhibition cabinet spaces in museums and art galleries.

Product Features

- Body Material: Aluminum alloy fixture body, glass optical device
- Optical System: Dual light distribution of lens and SUBROSA reflector
- Finish: Liquid paint, black (BK)
- Adjustable Angle: Horizontal adjustment from 0 ° to 365 °; Vertical 0-90 ° adjustment
- Accessories: As attached
- Certification: CQC
- IP Rating: IP20
- Insulation Level: Class III
- Operating Temperature: -20°C~40°C

Product Specifications

- LED Type: HP LED
- Light power: 3W
- Source Lm: 3000K:250LM; 4000K:265LM
- LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 3000K/4000K, Optional Ra90 or Ra97 (>Ra95)
- SDCM: 3 SDCM
- Input: 24VDC
- Dimming: On boarding knob dimming (range 10%~100%) or ON-OFF (supports system dimming, requires external dimmable constant voltage appliances, and matches the dimming system)
- Net Weight: About 0.07kg, without packaging

Order Model

Model	LED	Dimming	Beam	CRI	CCT	Finish
SL46F Ocularc Focus	LD03 LED 3W	O On-boarding	F 6-40°	9 90	30 3000K	BK Black
		E ON-OFF ^①	F 8-40°	A 97	40 4000K	
SL46F	LD03	O	F	9	30	BK

Example : SL46FLD03-O-F930BK

Note: ①Supports system dimming and requires an external dimmable constant voltage device (dimming method is determined by the constant voltage device)

OCULARC FOCUS - MODEL: SL46F

Mini Track Luminaires(24V)



PROJECT :

TYPE :

Accessories

<p>Low voltage track mini track Provide specifications of 1m, 2m, and 3m</p> <p>MT1M-BK-C 1m track MT2M-BK-C 2m track MT3M-BK-C 3m track</p>		<p>Track power supply end MLE-BK-C</p>
<p>Type I track connector MI-BK-C</p>		<p>Type L track connector ML-BK-C</p>


Note: The low-voltage track adopts surface installation and comes with two end caps; If hanging installation is required for low-voltage tracks, please contact WAC.

LIGHT DISTRIBUTION@3000K LUMINAIRE DATA

	<p>MODEL : SL46FLD03-O-F930(min)</p> <p>BEAM ANGLE : 6°</p> <p>POWER : 4W</p> <p>LUMENS : 44lm</p> <p>CBCP : 2069cd</p> <p>EFFICACY : 11lm/W</p>		<p>MODEL : SL46FLD03-O-F930(max)</p> <p>BEAM ANGLE : 40°</p> <p>POWER : 4W</p> <p>LUMENS : 138lm</p> <p>CBCP : 348cd</p> <p>EFFICACY : 35lm/W</p>
--	--	--	---

System Dimming Wiring Diagram (Fixture Model: SL46FLD03-E)

This circuit lighting fixture can support system dimming, and the wiring diagram is as follows (the dimming method is determined by the constant voltage electrical appliance). It is necessary to conduct dimming matching tests in advance.



OCULARC FOCUS - MODEL: SL47F

Mini Track Luminaires(24V)

WAC


PROJECT :

TYPE :

Product Image



Line Drawing



Product Description

The Ocularc Focus series low-voltage track lighting fixtures are suitable for WAC mini track systems, with flexible and compact lighting fixtures; Adopting WAC's leading SUBROSA dimming technology with a built-in 30 ° anti glare angle, achieving the ultimate anti glare effect; It can adjust the beam angle infinitely to meet the needs of different application environments and is widely used in exhibition cabinet spaces in museums and art galleries.

Product Features

- Body Material: Aluminum alloy fixture body, glass optical device
- Optical System: Dual light distribution of lens and SUBROSA reflector
- Finish: Liquid paint, black (BK)
- Adjustable Angle: Horizontal adjustment from 0 ° to 365 °; Vertical 0-90 ° adjustment
- Accessories: As attached
- Certification: CQC
- IP Rating: IP20
- Insulation Level: Class III
- Operating Temperature: -20°C~40°C

Product Specifications

- LED Type: HP LED
- Light power: 5W
- Source Lm: 3000K:480LM; 4000K:520LM
- LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 3000K/4000K, Optional Ra90 or Ra97 (>Ra95)
- SDCM: 3 SDCM
- Input: 24VDC
- Dimming: On boarding knob dimming (range 10%~100%) or ON-OFF (supports system dimming, requires external dimmable constant voltage appliances, and matches the dimming system)
- Net Weight: About 0.10kg, without packaging

Order Model

Model	LED	Dimming	Beam	CRI	CCT	Finish
SL47F Ocularc Focus	LD05 LED 5W	O On-boarding	F 8-40°	9 90	30 3000K	BK Black
		E ON-OFF ^①		A 97	40 4000K	
SL47F	LD05	O	F	9	30	BK

Example : SL47FLD05-O-F930BK

Note: ①Supports system dimming and requires an external dimmable constant voltage device (dimming method is determined by the constant voltage device)

OCULARC FOCUS - MODEL: SL47F

Mini Track Luminaires(24V)



PROJECT :



TYPE :

Accessories

<p>Low voltage track Mini track Provide specifications of 1m, 2m, and 3m</p> <p>MT1M-BK-C 1m track MT2M-BK-C 2m track MT3M-BK-C 3m track</p>		<p>Track power supply end MLE-BK-C</p> 
<p>Type I track connector MI-BK-C</p> 		<p>Type L track connector ML-BK-C</p> 


Note: The low-voltage track adopts surface installation and comes with two end caps; If hanging installation is required for low-voltage tracks, please contact WAC.

LIGHT DISTRIBUTION@3000K LUMINAIRE DATA

	<p>MODEL : SL47FLD05-O-F930(min)</p> <p>BEAM ANGLE : 8°</p> <p>POWER : 5.5W</p> <p>LUMENS : 58lm</p> <p>CBCP : 1599cd</p> <p>EFFICACY : 11lm/W</p>		<p>MODEL : SL47FLD05-O-F930(max)</p> <p>BEAM ANGLE : 40°</p> <p>POWER : 5.5W</p> <p>LUMENS : 167lm</p> <p>CBCP : 536cd</p> <p>EFFICACY : 30lm/W</p>
---	--	---	---

System Dimming Wiring Diagram (Fixture Model: SL47FLD05-E)

This circuit lighting fixture can support system dimming, and the wiring diagram is as follows (the dimming method is determined by the constant voltage electrical appliance). It is necessary to conduct dimming matching tests in advance.



OCULARC FOCUS - MODEL: SL48F

Mini Track Luminaires(24V)

WAC


PROJECT :

TYPE :

Product Image



Line Drawing



Product Description

The Ocularc Focus series low-voltage track lighting fixtures are suitable for WAC mini track systems, with flexible and compact lighting fixtures; Adopting WAC's leading SUBROSA dimming technology with a built-in 30 ° anti glare angle, achieving the ultimate anti glare effect; It can adjust the beam angle infinitely (By pulling) to meet the needs of different application environments and is widely used in exhibition cabinet spaces in museums and art galleries.

Product Features

- Body Material: Aluminum alloy fixture body, glass optical device
- Optical System: Dual light distribution of lens and SUBROSA reflector
- Finish: Liquid paint, black (BK)
- Adjustable Angle: Horizontal adjustment from 0 ° to 365 °; Vertical 0-90 ° adjustment
- Accessories: As attached
- Certification: CQC
- IP Rating: IP20
- Insulation Level: Class III
- Operating Temperature: -20°C~40°C

Product Specifications

- LED Type: HP LED
- Light power: 10W
- Source Lm: 3000K:950LM; 4000K:1000LM
- LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 3000K/4000K, Optional Ra90 or Ra97 (>Ra95)
- SDCM: 3 SDCM
- Input: 24VDC
- Dimming: On boarding knob dimming (range 10%~100%) or ON-OFF (supports system dimming, requires external dimmable constant voltage appliances, and matches the dimming system)
- Net Weight: About 0.2kg, without packaging

Order Model

Model	LED	Dimming	Beam	CRI	CCT	Finish
SL48F Ocularc Focus	LD10 LED 10W	O On-boarding	F 7-60°	9 90	30 3000K	BK Black
		E ON-OFF ^①		A 97	40 4000K	
SL48F	LD10	O	F	9	30	BK

Example : SL48FLD10-O-F930BK

Note: ①Supports system dimming and requires an external dimmable constant voltage device (dimming method is determined by the constant voltage device)

OCULARC FOCUS - MODEL: SL48F

Mini Track Luminaires(24V)



PROJECT :

TYPE :

Accessories

<p>Low voltage track Mini track Provide specifications of 1m, 2m, and 3m</p> <p>MT1M-BK-C 1m track MT2M-BK-C 2m track MT3M-BK-C 3m track</p>		<p>Track power supply end MLE-BK-C</p>	
<p>Type I track connector MI-BK-C</p>		<p>Type L track connector ML-BK-C</p>	

Note: The low-voltage track adopts surface installation and comes with two end caps; If hanging installation is required for low-voltage tracks, please contact WAC.

LIGHT DISTRIBUTION@3000K LUMINAIRE DATA

	<p>MODEL : SL48FLD10-O-F930(min)</p> <p>BEAM ANGLE : 7°</p> <p>POWER : 11W</p> <p>LUMENS : 211lm</p> <p>CBCP : 6643cd</p> <p>EFFICACY : 19lm/W</p>		<p>MODEL : SL48FLD10-O-F930(max)</p> <p>BEAM ANGLE : 60°</p> <p>POWER : 11W</p> <p>LUMENS : 440lm</p> <p>CBCP : 653cd</p> <p>EFFICACY : 40lm/W</p>
--	--	--	--

System Dimming Wiring Diagram (Fixture Model: SL48FLD10-E)

This circuit lighting fixture can support system dimming, and the wiring diagram is as follows (the dimming method is determined by the constant voltage electrical appliance). It is necessary to conduct dimming matching tests in advance.

