LIGNE PRO - MODEL: LP301

WAC LIGHTING

Responsible Lighting®


Linear Luminaires

PROJECT: TYPE:

Product Image

Line Drawing





Product Description

The LED panels in the LIGNE PRO series feature high luminous efficacy which blends perfectly with the ceiling after installation. The series also has good anti-glare performance and color consistency control for a comfortable light output. Ideal for indoor areas such as offices.

Product Features

Body Material: Aluminum extruded Optical System: Lens + Anti-glare reflector Finish: Electrostatic powder coating Adjustable Angle: Vertical 0°~30° adjustments Accessories: / Certification: CCC IP Rating: IP20 Insulation Level Class II

-20°C~40°C

Product Specifications

• Cut-out:	/
• Ceiling Thickness	/
• UGR:	<15
• LED Type:	SMD

Source Lm:	3000K: 32W 5600lm; 48W 8400lm;
	4000K: 32W 6160lm; 48W 9240lm;

5000K: 32W 6600lm; 48W 9800lm;

• LED Lifetime: >36000h-L70 /B10-Ta25°C(LM-80/TM-21)
• CCT/CRI: 2700K/ 3000K/3500K/4000K/5000K, CRI≥90

• Input: 220V AC / 50Hz

• **Dimming:** No dimming / 0~10V (Must be tested in

advance with the project site system for

matching)

• Net Weight: 1.2 Kg without packing

Order Model

Model	LED Power	Driver	ССТ	Beam	Reflector	Finish
LP301	LD32 32W	E On-Off	30 3000K			WT White
Linear Downlight	LM45 45W	D 0-10V Dimming	40 4000K	9 90°	P Panel	BK Black
			50 5000K			
	LM45 45W	N No Driver				

Example: LP301-LD32E-930PWT

• Operating Temperature:

Accessory

WAC Lighting
www.waclighting.com (US)
www.waclighting.com.cn (China)

Headquarters

44 Harbor Park Drive • Port Washington, NY Phone (516) 515.5000 • Fax (516) 515.5050

WAC Lighting(Shanghai)

14,Lane 299, Bi Sheng Road,Shanghai 201204 Phone (86.21) 3393.3558 • Fax (86.21) 3362.1598