

PLANA PRO - MODEL: SDL22

Ceiling Mount Luminaires



PROJECT:

TYPE:

Product Image



Line Drawing



Product Description

The PLANA PRO surface mounted tube light is exquisite and simple, with precise light distribution. It adopts SUBROSA hidden light technology and has the ultimate anti glare effect. Mainly suitable for hotels and commercial public spaces.

Product Features

- Body Material: Aluminum alloy extruded lamp body
- Optical System: Lenns+ SUBROSA optical system
- Finish: Static electricity powder coating
- Projection direction: /
- Accessories/Brackets: need to order separately
- Certification: CCC
- IP Rating: IP20
- Insulation Level: Class I
- Operating Temperature: -20°C~40°C

Product Specifications

- Shielding Angle: 35°
- LED Type: COB LED
- Source Lm: 1100 LM/10W 3000K
- LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 2700K/3000K/3500K/4000K/5000K, Ra90
- SDCM: 3 SDCM
- Input: 220V-240V AC /50Hz
- Dimming: No dimming/0-10V (must be matched with the project site system in advance Testing)
- Net Weight: 0.4Kg without packing


Order Model

Model	Size	Trim	LED	Driver	Beam	CCT	Reflector	Finish
SDL	2	2	LM10	E ON-OFF	1 15°	27 2700K	B Black	WT White
Surface	2"	Round	COB 10W	D 0-10V	2 24°	30 3000K	S Specular	BK Black
Mount		Trimless		Dimming	3 36°	35 3500K		
Downlight					4 48°	40 4000K		
						50 5000K		

Example: SDL22-LM10E-230SWT

Accessory

LENS-SDL22-HCM
Honeycomb



PLANA PRO - MODEL: SDL22


Ceiling Mount Luminaires




PROJECT:

TYPE:


LIGHT DISTRIBUTION@3000K LUMINAIRE DATA




MODEL: SDL22-LM10E-130SWT
BEAM ANGLE: 15°
POWER: 12W
LUMENS: 751lm
CBCP: 6612cd
EFFICACY: 63lm/W



MODEL: SDL22-LM10E-230SWT
BEAM ANGLE: 24°
POWER: 12W
LUMENS: 1054lm
CBCP: 5452cd
EFFICACY: 88lm/W



MODEL: SDL22-LM10E-330SWT
BEAM ANGLE: 36°
POWER: 12W
LUMENS: 1054lm
CBCP: 2554cd
EFFICACY: 88lm/W



MODEL: SDL22-LM10E-530SWT
BEAM ANGLE: 50°
POWER: 12W
LUMENS: 742lm
CBCP: 1176cd
EFFICACY: 62lm/W