SHINE PRO - MODEL: EF1S12

Flood Luminaires




	1	
PROJECT:	TYPE:	
	 1	

Product Image



Line Drawing





Product Description

SHINE PRO series is a professional LED floodlight designed by WAC for high-end outdoor lighting venues; Carefully designed with a unique appearance and a full glass surface design, it is simple and elegant, fashionable and beautiful, more suitable for current and future architectural trends. The lighting fixtures are equipped with W-Module modular design; Equipped with a breathing valve, it can effectively balance the internal and external air pressure to prevent condensation water; Fully integrating the principles of aerodynamics, creating the optimal heat dissipation structure, enhancing the heat dissipation performance of lighting fixtures, and extending the service life of LED lighting fixtures; Can precisely adjust the irradiation angle while designing a thoughtful angle locking structure to lock the projection direction; The SHINE PRO series lamps come in various sizes, angles, and power options to meet different lighting application solutions.

Product Features

• Body Material: Die cast aluminum alloy lamp body, base, and stainless steel fixed chassis • Optical System: Lens+ W-Module • Finish: Static electricity powder coating Vertical direction 0-90°, horizontal · Adjustable Angle: direction 0-330° • Accessories: As attached • Certification: **CCC** • IP Rating: IP65 • Insulation Level: Class I -20°C~50°C • Operating Temperature:

Product Specifications

• LED Type:	HP LED
• LED Power:	26.4W
• Sourse Lm:	2700K 2926lm;3000K 3080lm;4000K 3234lm
• LED Lifetime:	>50000h-L70 /B10-Ta25°C(LM-80/TM-21)
• CCT/CRI:	2700K, Ra80/3000K, Ra80/4000K,
	Ra80
• SDCM:	3SDCM(Mono)
• Input:	220V/AC 50/60Hz
• Dimming:	ON-OFF /DMX 512
• Net Weight:	5.8KG without packing

Order Model

Model	Power	LEDs	Max Lumens	Control Systems	Beam	CCT	Finish
	(W)	(quantity)	(lm)				
				EL ON OEE		27 2700K	
				EL ON-OFF	V 4°	30 3000K	BK Black
EF1S12-028	26.4(Max)	12	2016	220V/AC Power Supply		40 4000K	
				ML DMX512 Dimming		FC RGB	
				220V/AC Power		FW	
				Supply		RGBW=3000K	

Example: EF1S12-028EL-V30BK

WAC Lighting Headquarters WAC Lighting(Shanghai)

www.waclighting.com (US) 44 Harbor Park Drive • Port Washington, NY

www.waclighting.com.cn (China) Phone (516) 515.5000 • Fax (516) 515.5050 Phone (86.21) 3393.3558 • Fax (86.21) 3362.1598

SHINE PRO - MODEL: EF1S12

Flood Luminaires




PROJECT:	TYPE:	
A		· ·

Accessories

ITEM	Abbreviate	PIC	Model
Wall Washer Visor	ww		EF1S-WW1-BK
Stainless plate with Spike	SPK	Ţ	EF1S-SPK-BK
Adaptor For Pole	АР	7	EF1S-AP1-BK

LIGHT DISTRIBUTION@3000K LUMINAIRE DATA



 MODEL:
 EF1S12-028EL-V30BK

 BEAM ANGLE:
 4°

 POWER:
 33.3W (Max)

 LUMENS:
 2016Lm

 CBCP:
 /

 EFFICACY:
 60.5Lm/W

SHINE PRO - MODEL: EF1L24

Flood Luminaires



242

PROJECT:	TY	/PE:
Product Image	Line Drawing	
000000 000000	280	60

Product Description

SHINE PRO series is a professional LED floodlight designed by WAC for high-end outdoor lighting venues; Carefully designed with a unique appearance and a full glass surface design, it is simple and elegant, fashionable and beautiful, more suitable for current and future architectural trends. The lighting fixtures are equipped with W-Module modular design; Equipped with a breathing valve, it can effectively balance the internal and external air pressure to prevent condensation water; Fully integrating the principles of aerodynamics, creating the optimal heat dissipation structure, enhancing the heat dissipation performance of lighting fixtures, and extending the service life of LED lighting fixtures; Can precisely adjust the irradiation angle while designing a thoughtful angle locking structure to lock the projection direction; The SHINE PRO series lamps come in various sizes, angles, and power options to meet different lighting application solutions.

Product Features

• Body Material: Die cast aluminum alloy lamp body, base, and stainless steel fixed chassis • Optical System: Lens+ W-Module • Finish: Static electricity powder coating • Adjustable Angle: Vertical direction 0-90°, horizontal direction 0-330 ° • Accessories: As attached • Certification: CCC • IP Rating: IP65 • Insulation Level: Class I • Operating Temperature: -20°C~50°C

Product Specifications

• LED Type:

Ø168

J 1			
• LED Power:	26.4W		
• Sourse Lm:	2700K 2926lm;3000K 3080lm;4000K 3234lm		
• LED Lifetime:	>50000h-L70 /B10-Ta25°C(LM-80/TM-21)		
• CCT/CRI:	$2700\mbox{\ensuremath{\mbox{K}}}$, $\mbox{\ensuremath{\mbox{Ra}80}}\xspace / 3000\mbox{\ensuremath{\mbox{K}}}$, $\mbox{\ensuremath{\mbox{Ra}80}}\xspace / 4000\mbox{\ensuremath{\mbox{K}}}$,		
	Ra80		
• SDCM:	3SDCM(Mono)		
• Input:	220V/AC 50/60Hz		
• Dimming:	ON-OFF /DMX 512		
 Net Weight: 	5.8KG without packing		

HP LED

Order Model

N	Iodel	Power (W)	LEDs (quantity)	Max Lumens (lm)	Control Systems	Beam	CCT	Finish
E	F1L24-056	52.8(Max)	24	3482	EL ON-OFF 220V/AC Power Supply ML DMX512 Dimming 220V/AC Power Supply	V 4°	27 2700K 30 3000K 40 4000K FC RGB FW RGBW=3000K	BK Black

Example: EF1L24-056EL-V30BK

WAC Lighting Headquarters WAC Lighting(Shanghai)

www.waclighting.com (US) 44 Harbor Park Drive • Port Washington, NY

www.waclighting.com.cn (China) Phone (516) 515.5000 • Fax (516) 515.5050 Phone (86.21) 3393.3558 • Fax (86.21) 3362.1598

SHINE PRO - MODEL: EF1L24

Flood Luminaires



PROJECT:	TYPE:
Accessories	

ITEM	Abbreviate	PIC	Model
Wall Washer Visor	WW		EF1L-WW1-BK
Stainless plate with Spike	SPK	Ţ	EF1L-SPK-BK
Adaptor For Pole	AP	1	EF1L-AP1-BK

LIGHT DISTRIBUTION@3000K LUMINAIRE DATA

