

PLANA SMART - MODEL: DDP81

Recessed Luminaires

WAC


PROJECT:

TYPE:

Product Image



Line Drawing



Product Description

PLANA Smart series intelligent remote control tube light is exquisite and simple, and can be adjusted horizontally and vertically through a stepper motor. Combined with various intelligent control systems, it is very convenient and flexible to use; Simultaneously possessing precise light distribution and ultimate anti glare effect. Mainly suitable for places such as art museums and large conference halls.

Product Features

- Body Material: Aluminum alloy lamp body
- Optical System: Lens
- Finish: Electrostatic powder coating
- Adjustable Angle: Horizontal 0-355 °, vertical 0-30 °
- Accessories: Equipped with anti glare honeycomb
- Certification: CCC/CE
- IP Rating: IP20
- Insulation Level: Class I
- Operating Temperature: -20°C~40°C

Product Specifications

- Cut-out: Ø200mm
- Ceiling Thickness: 1mm~26mm
- Shielding Angle: 15°
- LED Type: HP LED (7°) and COB (12°, 24°, 36°)
- Source Lm: 3000K: 2750lm/25W; 3850lm/35W;
- LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 2700K / 3000K/ 4000K, Ra90
- SDCM: 3 SDCM
- Input: 220V~240V AC / 50Hz
- Dimming: Remote control (Projection direction adjustment & Dimming)
APP (Projection direction adjustment & Dimming, Bluetooth wireless transmission)
0-10V+ remote control (Dimming+ Projection direction adjustment)
DMX512+ Remote control (Dimming+ Projection direction adjustment)
DMX512 (Projection direction adjustment & Dimming)
(All of the above must undergo compatibility testing with the project site system in advance)
- Net Weight: Approximately 3.4kg without packing

PLANA SMART - MODEL: DDP81

Recessed Luminaires

WAC

PROJECT:


TYPE:

Order Model

Model	Size	Trim	LED	Driver	Beam	CCT	Reflector	Finish
DDP Plana Smart	8 8"	1 Round Trim	LM25 25W LM35 35W	B App	S 7° 1 12° 2 24° 3 36°	27 2700K 30 3000K 40 4000K	W White	WT White
				G Remote control				
				D 0-10V+Remote control			B Black	BK Black
				M DMX512+Remote control				
				W DMX512				

Example: DDP81-LM25G-130WWT

Accessory

Remote control	PAD-TL58S-WT Handheld remote control	
----------------	--	---

Note: The handheld remote control needs to be ordered separately, with a maximum number of 10 paired lamps and a maximum distance of 10 meters. Please refer to the installation manual for details.