

# MINI FLOOD IV - MODEL: ELF6

Linear Luminaires

# WAC


PROJECT:

TYPE:

## Product Image



## Line Drawing



## Product Description

Beacon-Mini Flood IV series of lights feature high-quality chips that offer efficient light output and long lifespan, along with lenses that boast unique optical properties, with their evenly spaced arrangement, they ensure even illumination. With an IP66 waterproof rating and 0-10V/DMX512 dimming control, the Mini Flood IV series of lights feature both bottom and side outlets, complying with the power consumption design requirements of LED outdoor lighting. The transparent end caps allow for continuous splicing, ensuring consistent illumination at the spliced area of the lights. The color light version features a constant wattage module, maximizing the power output of the lights and effectively reducing energy consumption.

## Product Features

- Body Material: Aluminum extruded lamp body+PC94V0 end cap
- Optical System: Lens
- Finish: Static electricity powder coating
- Adjustable Angle: /
- Accessories: Rotating bracket, adjustable angle+/-90 °; Fixed bracket
- Certification: CQC
- IP Rating: IP66
- Insulation Level: Class III
- Operating Temperature: -20°C~50°C

## Product Specifications

- LED Type: High Power
- LED Power: 48W (MONO) /1000mm ,48W (RGBW) /1000mm
- Source Lm: 2700K: 5280lm;3000K: 5520lm;4000K: 5760lm
- LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 2700K / 3000K / 4000K / Ra90, RGBW
- Source SDCM: 3 SDCM (MONO), 5 SDCM (RGBW)
- Input: 24V DC /
- Dimming: ON-OFF / 0-10V /DMX512
- Net Weight: 1.3Kg/M without packing

## Order Model

Model	Length/mm	Power/W	LEDs (quantity)	Max Lumens/ lm	Control Systems	Beam	Power Feed Type	CCT	Finish
ELF603-06	250	6(Max)	6	503	ET ON-OFF 24V DC Power Supply	V 6° S 9° J 14x40°	B Bottom S Side	27 2700K	BK Black
ELF603-09	250	9(Max)	6	755				30 3000K	
ELF603-12	250	12(Max)	6	1006				40 4000K	
ELF605-12	500	12(Max)	9	1006	DT 0-10V Dimming 24V DC Power Supply	J 14x40°	B Bottom S Side	27 2700K	
ELF605-18	500	18(Max)	12	1509				30 3000K	
ELF605-24	500	24(Max)	15	2012				40 4000K	
ELF610-24	1000	24(Max)	18	2011	MT DMX512 Dimming 24V DC Power Supply	J 14x40°	B Bottom S Side	27 2700K	
ELF610-36	1000	36(Max)	24	3017				30 3000K	
ELF610-48	1000	48(Max)	30	4023				40 4000K	

Example: ELF610-48ET-VB27BK

WAC Lighting  
www.waclighting.com (US)  
www.waclighting.com.cn (China)

Headquarters  
44 Harbor Park Drive • Port Washington, NY  
Phone (516) 515.5000 • Fax (516) 515.5050

WAC Lighting (Shanghai)  
14, Lane 299, Bi Sheng Road, Shanghai 201204, China  
Phone (86.21) 3393.3558 • Fax (86.21) 3362.1598

# MINI FLOOD IV - MODEL: ELF6

Linear Luminaires



PROJECT:

TYPE:

Model	Length/mm	Power/W	LEDs (quantity)	Max Lumens/ lm	Control Systems	Beam	Power Feed Type	CCT	Finish
<b>ELF605</b>	500	24(Max)	12	693	MT DMX512 Dimming 24V DC Power Supply	1 19° 2 26° 3 39° 5 51° F 22x45°	B Bottom S Side	F3 RGBW 3000K F4 RGBW 4000K F6 RGBW 5700K	<b>BK</b> Black
<b>ELF610</b>	1000	48(Max)	24	1385					

Example: ELF610-48MT-1BF3BK

## Accessories

Item	Description	Pic	Mounting	Quantity Suggested
<b>ELF6-CB48025-BK</b>	Cover 250mm			
<b>ELF6-CB48050-BK</b>	Cover 500mm			
<b>ELF6-CB48100-BK</b>	Cover 1000mm			
<b>ELF6-GB48025-BK</b>	Grilling 250mm			RGBW VERSION ONLY SUITABLE FOR ELF6-GB36050-BK ELF6-GB36100-BK
<b>ELF6-GB24050-BK</b>	Grilling 12W 500mm			
<b>ELF6-GB36050-BK</b>	Grilling 18W 500mm			
<b>ELF6-GB48050-BK</b>	Grilling 24W 500mm			
<b>ELF6-GB24100-BK</b>	Grilling 24W 1000mm			
<b>ELF6-GB36100-BK</b>	Grilling 36W 1000mm			
<b>ELF6-GB48100-BK</b>	Grilling 48W 1000mm			
<b>ELF5-PC-CT002F</b>	ET Female connector			
<b>ELF5-PC-CT002M</b>	ET Male connector			48W/M 1 pc per 4m 36W/M 1 pc per 6m 24W/M 1 pc per 8m
<b>ELF5-SC-CT002F</b>	MT Female connector			48W/M 1 pc per 4m 36W/M 1 pc per 6m 24W/M 1 pc per 8m
<b>ELF5-SC-CT002M</b>	MT Male connector			48W/M 1 pc per 4m 36W/M 1 pc per 6m 24W/M 1 pc per 8m

# MINI FLOOD IV - MODEL: ELF6


Linear Luminaires




PROJECT:

TYPE:


## LIGHT DISTRIBUTION@3000K LUMINAIRE DATA




**MODEL:** ELF610-48MT-1BF3BK  
**BEAM ANGLE:** 19 °  
**POWER:** 49.6W  
**LUMENS:** 1385lm  
**CBCP:** 5921cd  
**EFFICACY:** 27.9lm/W




**MODEL:** ELF610-48MT-2BF3BK  
**BEAM ANGLE:** 26 °  
**POWER:** 49.6W  
**LUMENS:** 1476lm  
**CBCP:** 4077cd  
**EFFICACY:** 29.8lm/W




**MODEL:** ELF610-48MT-3BF3BK  
**BEAM ANGLE:** 39 °  
**POWER:** 49.6W  
**LUMENS:** 1578lm  
**CBCP:** 2563cd  
**EFFICACY:** 31.8lm/W




**MODEL:** ELF610-48MT-5BF3BK  
**BEAM ANGLE:** 51 °  
**POWER:** 49.6W  
**LUMENS:** 1396lm  
**CBCP:** 1525cd  
**EFFICACY:** 28.1lm/W




**MODEL:** ELF610-48MT-FBF3BK  
**BEAM ANGLE:** 22X45 °  
**POWER:** 49.6W  
**LUMENS:** 1390lm  
**CBCP:** 2922cd  
**EFFICACY:** 28lm/W



**MODEL:** ELF610-48ET-VB30BK  
**BEAM ANGLE:** 6 °  
**POWER:** 54.9W  
**LUMENS:** 3876lm  
**CBCP:** /  
**EFFICACY:** 70.1lm/W



**MODEL:** ELF610-48ET-SB30BK  
**BEAM ANGLE:** 9 °  
**POWER:** 54.9W  
**LUMENS:** 4023lm  
**CBCP:** /  
**EFFICACY:** 73.1lm/W



**MODEL:** ELF610-48ET-FB30BK  
**BEAM ANGLE:** 14X40 °  
**POWER:** 54.7W  
**LUMENS:** 3538lm  
**CBCP:** /  
**EFFICACY:** 64.6lm/W

# MINI FLOOD IV - MODEL: ELF7

Linear Luminaires

# WAC


PROJECT:

TYPE:

## Product Image



## Line Drawing



## Product Description

Beacon-Mini Flood IV series of lights feature high-quality chips that offer efficient light output and long lifespan, along with lenses that boast unique optical properties, with their evenly spaced arrangement, they ensure even illumination. With an IP66 waterproof rating and 0-10V/DMX512 dimming control, the Mini Flood IV series of lights feature both bottom and side outlets, complying with the power consumption design requirements of LED outdoor lighting. The transparent end caps allow for continuous splicing, ensuring consistent illumination at the spliced area of the lights. The color light version features a constant wattage module, maximizing the power output of the lights and effectively reducing energy consumption.

## Product Features

- Body Material: Aluminum extruded lamp body+PC94V0 end cap
- Optical System: Integrated lens
- Finish: Static electricity powder coating
- Adjustable Angle: /
- Accessories: Rotating bracket, adjustable angle+/-90 °; Fixed bracket
- Certification: CQC
- IP Rating: IP66
- Insulation Level: Class III
- Operating Temperature: -20°C~50°C

## Product Specifications

- LED Type: SMD
- LED Power: 24W (Max) /1000mm
- Source Lm: 2700K: 2400lm;3000K:2520lm;4000K: 2640lm
- LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 2700K / 3000K / 4000K / Ra90
- Source SDCM: 3 SDCM (MONO)
- Input: 24V DC
- Dimming: ON-OFF / 0-10V /DMX512
- Net Weight: 1.1Kg/M without packing

## Order Model

Model	Length/mm	Power/W	LEDs (quantity)	Max Lumens/ lm	Control Systems	Beam	Power Feed Type	CCT	Finish
ELF703-06	250	6(Max)	24	503	ET ON-OFF 24V DC Power Supply	11x64 ° Integrated lens	B Bottom S Side	27 2700K	BK Black
ELF705-12	500	12(Max)	48	1006	DT 0-10V Dimming 24V DC Power Supply			30 3000K	
ELF710-24	1000	24(Max)	96	2011	MT DMX512 Dimming 24V DC Power Supply			40 4000K	

Example: ELF710-24ET-1B30BK

WAC Lighting  
www.waclighting.com (US)  
www.waclighting.com.cn (China)

Headquarters  
44 Harbor Park Drive • Port Washington, NY  
Phone (516) 515.5000 • Fax (516) 515.5050

WAC Lighting (Shanghai)  
14, Lane 299, Bi Sheng Road, Shanghai 201204, China  
Phone (86.21) 3393.3558 • Fax (86.21) 3362.1598

# MINI FLOOD IV - MODEL: ELF7

Linear Luminaires




PROJECT:

TYPE:


## Accessories

Item	Description	Pic	Mounting	Quantity Suggested
ELF6-CB48025-BK	Cover 250mm			
ELF6-CB48050-BK	Cover 500mm			
ELF6-CB48100-BK	Cover 1000mm			
ELF5-PC-CT002F	ET Female connector			1 pc per 7m
ELF5-PC-CT002M	ET Male connector			1 pc per 7m
ELF5-SC-CT002F	MT Female connector			1 pc per 7m
ELF5-SC-CT002M	MT Male connector			1 pc per 7m

## LIGHT DISTRIBUTION@3000K LUMINAIRE DATA



<b>MODEL:</b>	ELF710-24MT-1B30BK
<b>BEAM ANGLE:</b>	11X64°
<b>POWER:</b>	26.9W
<b>LUMENS:</b>	1260 lm
<b>CBCP:</b>	/
<b>EFFICACY:</b>	46.83 lm /W



<b>MODEL:</b>	ELF610-48MT-5BF3BK
<b>BEAM ANGLE:</b>	20X87°
<b>POWER:</b>	25.7W
<b>LUMENS:</b>	853 lm
<b>CBCP:</b>	/
<b>EFFICACY:</b>	33.1 lm /W

WAC Lighting  
[www.waclighting.com](http://www.waclighting.com) (US)  
[www.waclighting.com.cn](http://www.waclighting.com.cn) (China)

Headquarters  
 44 Harbor Park Drive • Port Washington, NY  
 Phone (516) 515.5000 • Fax (516) 515.5050

WAC Lighting (Shanghai)  
 14, Lane 299, Bi Sheng Road, Shanghai 201204, China  
 Phone (86.21) 3393.3558 • Fax (86.21) 3362.1598