VOLTA SMART - MODEL: DDT69

WAC LIGHTING

Responsible Lighting®

Recessed Luminaires

| Project Name: | |
|---------------|--|
|---------------|--|

| Tvpe: | |
|-------|--|
| | |
| | |

Product Image







Product Description

VOLTA Smart Series Smart Remote Control Downlight, with delicate and simple design, enables horizontal and vertical adjustment by stepping motor with multiple intelligent control systems. Flexible and easy to use, with precise light distribution and ultimate anti-glare effect. Mainly used in art museums, large conference halls and other places.

| Product Features | 1 | Product Specifications | | | |
|-----------------------|---|------------------------|---|--|--|
| • Body Material: | Aluminum Alloy Lamp Body | •Cut-out: | Ø160mm | | |
| Optical System: | Lens | •Ceiling Thickness: | 1mm~25mm | | |
| • Finish: | Electrostatic Powder Coating | •Shading Angle: | 15° | | |
| Objection: | Vertical 0°~30° adjustment, Horizontal 0°~355° rotation | •LED Type: | HP LED (7°) and COB (10°、24°、36°) | | |
| Accessory: | See Attached | •Source Lm: | 3000K: 2250lm/20W; 3350lm/30W; | | |
| Certification: | ссс | •LED Lifetime: | >36000h-L70 /B10-Ta25°C(LM-80/TM-21) | | |
| • IP Rating: | IP20 | •CCT/CRI: | 2700K/ 3000K/3500K/ 4000K/5000K, CRI≥9 | | |
| Insulation Level: | Class I | •Input: | 220V AC / 50Hz | | |
| Operating Temperature | : -20°C∼40°C | •Dimming: | Remote control (projection direction adjustment & dimming) APP (projection direction adjustment & dimming, Bluetooth wireless transmission) 0-10V + remote control (dimming + projection direction adjustment) | | |
| | | | DMX512 + remote control (dimming + projection direction adjustment | | |
| | | | DMX512 (projection direction adjustment & dimming) All of the above must be done in advance with the project site system t | | |

•Net Weight:

Approx. 2.6Kg, without packaging

do the matching test

Order Model

| Model | Size | Trim | LED | Driver | Beam | ССТ | Reflector | Finish |
|-------------|------|------------|----------|-----------------|-----------------|-----------------|----------------|-----------------|
| DDT69 | 6 | 9 | LM20 20W | В Арр | S 7° | 27 2700K | W White | WT White |
| Volta Smart | 6 | Round Trim | LM30 30W | G Remote | 1 10° | 30 3000K | | |
| | | | | D 0-10V+Remote | 2 24° | 35 3500K | | |
| | | | | M DMX512 | 3 36° | 40 4000K | B Black | BK Black |
| | | | | +Remote | F 15-40° | 50 5000K | | |
| | | | | W DMX512 | | | | |
| | | | | | | | | |

Example: DDT69-LM20G-130WWT

Note: Handheld remote control to be ordered separately (Model: PAD-DDT69-WT, the maximum number of paired fixtures is 10, the longest distance is 10 meters, refer to the installation manual for details)

WAC Lighting www.waclighting.com (US) www.waclighting.com.cn (China) Headquarters 44 Harbor Park Drive • Port Washington, NY Phone (516) 515.5000 • Fax (516) 515.5050 WAC Lighting(Shanghai) 14,Lane 299, Bi Sheng Road,Shanghai 201204 Phone (86.21) 3393.3558 • Fax (86.21) 3362.1598