VOLO- MODEL: OC1N

WAC LIGHTING


Responsible Lighting®

Linear	Luminaires

Project Name:	Туре:	

Product Image Line Drawing





Product Description

VOLO Pendant Linear Light, with aluminum body, compact and aesthetic appearance. LED light source, with good heat dissipation. Energy efficient, good anti-glare, customized lengths and connectable at the beginning and end. Suitable for commercial office lighting applications.

Product Features

Body Materials:
 Aluminum Alloy Body

• Optical System: Anti-glare Panel

• Finishes: Electrostatic Powder Coating

• Objection Direction: /

• Accessory/Bracket:

• Certification: CCC
• IP Rating: IP20

• Insulation Level: Class I

. . .

• Operating Temperature: -20°C~40°C

Product Specifications

• Shading Angle: /

• **LED Type**: SMD LED

• Source Lm: /

• **LED Lifetime**: > 50,000h-L70 /B10-Ta25°C(LM-80/TM-21)

• **CCT/CRI:** 3000K/ 3500K/4000K/5000K, Ra90

• SDCM: 3 SDCM

• **Input**: 220V-240V AC / 50Hz

• **Dimming**: ON-OFF/0-10V/DALI (Matching tests

must be done with the project site systems)

• Net Weight: Approx. 1.5Kg, excluding packaging

Order Model

Model	Length(mm)	Power	Driver	Beam	ССТ	Finish
		(W)				
OC1N	12 1200	25 25W	E ON-OFF	P (Matte Cover)	30 3000K	WT White
			D 0-10V Dimming	Y (Prism Cover)	35 3500K	BK Black
			A DALI		40 4000K	
					50 5000K	

Example: OC1N-1225E-Y40WT

WAC Lighting www.waclighting.com (US) www.waclighting.com.cn (China) Headquarters

44 Harbor Park Drive

44 Harbor Park Drive • Port Washington, NY Phone (516) 515.5000 • Fax (516) 515.5050

WAC Lighting Technology (Shanghai) Co., Ltd 14, Lane 299, Bi Sheng Road, Shanghai 201204 Phone (86.21) 3393.3558 • Fax (86.21) 3362.1598