

# VOLO- MODEL: OC1L

## Linear Luminaires

# WAC LIGHTING



Responsible Lighting®

Project Name:

Type:

Product Image

Line Drawing



### Product Description

VOLO Pendant Linear Light, with aluminum body, compact and aesthetic appearance. LED light source, with good heat dissipation. Energy efficient, good anti-glare, customized lengths and connectable at the beginning and end. Suitable for commercial office lighting applications.

### Product Features

- **Body Materials:** Aluminum Extruded Lamp Body
- **Optical System:** Anti-glare Panel
- **Finishes:** Electrostatic Powder Coating
- **Objection Direction:** /
- **Accessory/Bracket:** /
- **Certification:** CCC
- **IP Rating:** IP20
- **Insulation Level:** Class I

### Product Specifications

- **Shading Angle:** /
- **LED Type:** SMD LED
- **Source Lm:** /
- **LED Lifetime:** > 50,000h-L70 /B10-Ta25°C(LM-80/TM-21)
- **CCT/CRI:** 3000K/ 3500K/4000K/5000K, Ra90
- **SDCM:** 3 SDCM
- **Input:** 220V-240V AC / 50Hz
- **Dimming:** ON-OFF/0-10V/DALI (Matching tests must be done with the project site systems)
- **Net Weight:** Approx. 2.7Kg, excluding packaging

### Order Model

Model	Length (mm)	Power (mm)	Driver	Beam	CCT	Finish
OC1L	12 1200	40 40W	E On-Off	P Matte Cover	30 3000K	WT White
			D 0-10V Dimming	Y Prism Cover	35 3500K	BK Black
			A DALI		40 4000K	
					50 5000K	

Example: OC1L-1240E-Y40WT