

SLANA LINEAR - MODEL: AES301G


Surface mounting Luminaires

WAC LIGHTING



PROJECT:

TYPE:

Product Image



Line Drawing



Product Description

Surface mounted linear down lighting fixtures, using SUBROSA hidden light technology, are more decorative in building lighting, with multiple light distribution and AC220V input. Exquisite and meticulous appearance and structural design, as well as excellent optical performance, can provide users with a perfect light environment experience, suitable for outdoor surface mounted applications.

Product Features

- Body Material: Aluminum alloy extruded lamp body
- Optical System: Lens+ SUBROSA optical system
- Finish: Static electricity powder coating
- Projection direction: /
- Accessories/Brackets: /
- Certification: CCC
- IP Rating: IP65
- Insulation Level: Class I
- Operating Temperature: -20°C~50°C

Product Specifications

- Shielding Angle: 35°
- LED Type: HIGH POWER LED
- Source Lm: 3000K 1000 LM, 4000K 1100LM;
- LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 3000K/4000K, Ra90
- SDCM: 3 SDCM
- Input: 220V-240V AC /50Hz
- Dimming: ON-OFF
- Net Weight: 0.55Kg without packing

Order Model

Model	Length (mm)	LED Power (W)	LEDs (Quantity)	Driver	Beam	CCT	Finish
AES301G Linear Graze Slana series Surface mounting	119mm	08 8W	4 pcs	EL ON-OFF 220V AC Power Supply	1 15° 2 26° 3 36°	30 3000K 40 4000K	WT White

Example: AES301G-08EL130WT

Accessory

WAC Lighting
www.waclighting.com (US)
www.waclighting.net (International)

Headquarters
44 Harbor Park Drive • Port Washington, NY
Phone (516) 515.5000 • Fax (516) 515.5050

WAC Lighting(Shanghai)
14,Lane 299, Bi Sheng Road, Shanghai 201204,China
Phone (86.21) 3393.3558 • Fax (86.21) 3362.1598

SLANA LINEAR - MODEL: AES301G


Surface mounting Luminaires

WAC LIGHTING


PROJECT:

TYPE:


LIGHT DISTRIBUTION@3000K LUMINAIRE DATA



MODEL:	AES301G-08EL130WT
BEAM ANGLE:	15.9°
POWER:	10.45W
LUMENS:	504.5 lm
CBCP:	/
EFFICACY:	48.3 lm/W



MODEL:	AES301G-08EL230WT
BEAM ANGLE:	26.9°
POWER:	10.45W
LUMENS:	464.8 lm
CBCP:	/
EFFICACY:	44.5 lm/W



MODEL:	AES301G-08EL330WT
BEAM ANGLE:	35.4°
POWER:	10.45W
LUMENS:	436.6 lm
CBCP:	/
EFFICACY:	41.8 lm/W

SLANA LINEAR - MODEL: AES303G


Surface mounting Luminaires

WAC LIGHTING


PROJECT:

TYPE:

Product Image



Line Drawing



Product Description

Surface mounted linear down lighting fixtures, using SUBROSA hidden light technology, are more decorative in building lighting, with multiple light distribution and AC 220V input. Exquisite and meticulous appearance and structural design, as well as excellent optical performance, can provide users with a perfect light environment experience, suitable for outdoor surface mounted applications.

Product Features

- Body Material: Aluminum alloy extruded lamp body
- Optical System: Lens+ SUBROSA optical system
- Finish: Static electricity powder coating
- Projection direction: /
- Accessories/Brackets: /
- Certification: CCC
- IP Rating: IP65
- Insulation Level: Class I
- Operating Temperature: -20°C~50°C

Product Specifications

- Shielding Angle: 35°
- LED Type: HIGH POWER LED
- Source Lm: 3000K 2000LM,4000K 2200LM;
- LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 3000K/4000K, Ra90
- SDCM: 3 SDCM
- Input: 220V-240V AC /50Hz
- Dimming: ON-OFF or 0-10V Dimming
- Net Weight: 0.7Kg without packing

Order Model

Model	Length (mm)	LED Power (W)	LEDs (Quantity)	Driver	Beam	CCT	Finish
AES303G Linear Graze Slana series Surface mounting	231mm	16 16W	8pcs	EL ON-OFF 220V AC Power Supply DL 0-10V Dimming 220V AC Power Supply	1 15° 2 26° 3 36°	30 3000K 40 4000K	WT White

Example: AES303G-16EL130WT

SLANA LINEAR - MODEL: AES303G

Surface mounting Luminaires


WAC LIGHTING

PROJECT:


TYPE:

Accessory


LIGHT DISTRIBUTION@3000K LUMINAIRE DATA



MODEL:	AES303G-16EL130WT
BEAM ANGLE:	15.8 °
POWER:	19.7W
LUMENS:	958 lm
CBCP:	/
EFFICACY:	48.6 lm/W



MODEL:	AES303G-16EL230WT
BEAM ANGLE:	26.9 °
POWER:	19.7W
LUMENS:	962.3 lm
CBCP:	/
EFFICACY:	48.9 lm/W



MODEL:	AES303G-16EL330WT
BEAM ANGLE:	35 °
POWER:	19.7W
LUMENS:	851 lm
CBCP:	/
EFFICACY:	43.2 lm/W

SLANA LINEAR - MODEL: AES305G

Surface mounting Luminaires



WAC LIGHTING

PROJECT:

TYPE:

Product Image

Line Drawing



Product Description

Surface mounted linear down lighting fixtures, using SUBROSA hidden light technology, are more decorative in building lighting, with multiple light distribution and AC220V input. Exquisite and meticulous appearance and structural design, as well as excellent optical performance, can provide users with a perfect light environment experience, suitable for outdoor surface mounted applications.

Product Features

- Body Material: Aluminum alloy extruded lamp body
- Optical System: Lens+ SUBROSA optical system
- Finish: Static electricity powder coating
- Projection direction: /
- Accessories/Brackets: /
- Certification: CCC
- IP Rating: IP65
- Insulation Level: Class I
- Operating Temperature: -20°C~50°C

Product Specifications

- Shielding Angle: 35°
- LED Type: HIGH POWER LED
- Source Lm: 3000K 4000LM, 4000K 4400LM;
- LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)
- CCT/CRI: 3000K/4000K, Ra90
- SDCM: 3 SDCM
- Input: 220V-240V AC /50Hz
- Dimming: ON-OFF or 0-10V Dimming
- Net Weight: 1.2Kg without packing

Order Model

Model	Length (mm)	LED Power (W)	LEDs (Quantity)	Driver	Beam	CCT	Finish
AES305G				EL ON-OFF 220V AC Power Supply	1 15°	30 3000K	WT
Linear Graze				DL 0-10V Dimming 220V AC Power Supply	2 26°	41 4000K	White
Slana series	455mm	32 32W	16pcs		3 36°		
Surface mounting							

Example: AES305G-32EL130WT

SLANA LINEAR - MODEL: AES305G

Surface mounting Luminaires


WAC LIGHTING

PROJECT:


TYPE:

Accessory


LIGHT DISTRIBUTION@3000K LUMINAIRE DATA



MODEL:	AES305G-32EL130WT
BEAM ANGLE:	15.9°
POWER:	36.6W
LUMENS:	1920 lm
CBCP:	/
EFFICACY:	52.5 lm/W



MODEL:	AES305G-32EL230WT
BEAM ANGLE:	26.9°
POWER:	36.6W
LUMENS:	1871 lm
CBCP:	/
EFFICACY:	51.1 lm/W



MODEL:	AES305G-32EL330WT
BEAM ANGLE:	36°
POWER:	36.6W
LUMENS:	1642 lm
CBCP:	/
EFFICACY:	44.88 lm/W