SHINE PRO CEILING WASH - MODEL: AEW3C

Wall Luminaires


WAC LIGHTING

Type:

Product Image



Line Drawing



Product Description

The SHINE PRO wall mounted ceiling wash light is more decorative in architectural lighting. The wall-mounted, ultra-thin and streamlined design integrates well with the overall space. The luminaire is equipped with both horizontal and vertical light distribution systems, combined with an angled structural design. Excellent optical performance and flexible humanized installation accessories can bring users a perfect light environment experience, suitable for public high space functional lighting.

Product Features

· Body Material: Aluminum Die-casting Lamp Body

• Optical System: Reflector

• Finish: Electrostatic Powder Coating

• **Projection Angle:** Vertical $\pm 15^{\circ}$ adjustment

Accessory/Bracket: /Certification: CCCIP Rating: IP65

• Insulation Class: Class I

• Operating Temperature: -20°C~50°C

Product Specifications

• LED Type: COB

• **Power:** 39.1W (Max)

Source Lm: 2700K 3564lm; 3000K 3864lm; 4000K 4104lm
 LED Lifetime: >50000h-L70 /B10-Ta25°C(LM-80/TM-21)

• CCT/CRI: 2700K /3000K /3500K /4000K /5000K, Ra90

• SDCM: 3 SDCM (MONO)

• Input: 220VC

Dimming: ON-OFF or 0-10V dimming control
 Net Weight: Approx. 2.6Kg, excluding packaging

Order Model

Mo	odel	Comment	Power (W)	LEDs (quantity)	Max Lumens (Im)	Control Systems	Beam	сст	Finish
AE	W 3	C Ceiling Wash	40 40(Max)	СОВ	2609	EL ON-OFF 220V AC Power Supply DL 0-10V Dimming 220V AC Power Supply	U Washer (1:3) W Washer (1:4.5)	27 2700K 30 3000K 35 3500K 40 4000K 50 5000K	WT White

Example: AEW3C-40ELU27BK

Note: The wall-washing ratio refers to the distance between the fixture from the ceiling and the ratio of the distance between the two fixtures installed, see the installation instructions.

SHINE PRO CEILING WASH - MODEL: AEW3C


Wall Luminaires

WAC LIGHTING

Project Name:	Туре:	

Accessory

Light Distribution@3000K Data



MODEL:

BEAM ANGLE:

POWER:

LUMENS:

CBCP:

EFFICACY:


AEW3C-40ELU27BK

18°X100° Polarized 72°

41.3W

2019lm

49lm/W



MODEL:

AEW3C-40ELW27BK

24°X120° Polarized 66° **BEAM ANGLE:**

41W POWER:

LUMENS: 2609lm

CBCP:

63.6lm/W



U-shaped Light Distribution



W-shaped Light Distribution